

CovT Mono



Professional architectural linear light system surface mounted for Cove light, made of extruded aluminium adapt for Indoor applications, diffuser made on polycarbonate (PC) UV resistance, available in 5 different lengths, anodized aluminium finish. Included with cable Male & Female, cable length 100mm for easy connection loop.


LED mono-colour, diffused light effect, with LEDs rigid circuit, high performance with CRI>95, 24Volt Constant Voltage, 25Watt/Meter with SDCM<3 (One Bin Only), lumen and available CCT as reported below.

Impact IK08 and protection IP44

Operating ambient temperature from -20°C / +40°C

Produced in Italy.

Image & Drawing



Product Final Code

CCT	1 ft / 305mm	2 ft / 610mm	3 ft / 915mm	4 ft / 1220mm	5 ft / 1525mm
2700K	L-CovT1.AN.27K	L-CovT2.AN.27K	L-CovT3.AN.27K	L-CovT4.AN.27K	L-CovT5.AN.27K
3000K	L-CovT1.AN.30K	L-CovT2.AN.30K	L-CovT3.AN.30K	L-CovT4.AN.30K	L-CovT5.AN.30K
4000K	L-CovT1.AN.40K	L-CovT2.AN.40K	L-CovT3.AN.40K	L-CovT4.AN.40K	L-CovT5.AN.40K



CovT Mono

Lumen Output LED

Length	Wattage	<u>2700K</u>	<u>3000K</u>	<u>4000K</u>
1 ft / 305mm	7	605	605	706
2 ft / 610mm	14	1210	1210	1411
3 ft / 915mm	21	1814	1814	2117
4 ft / 1220mm	28	2419	2419	2822
5 ft / 1525mm	35	3024	3024	3528

Technical Data

Application	Surface Mounted
Finish	Aluminum Anodized
Dimension mm	26 x 310 - 610 - 915 - 1220 - 1525 & Custom
Fitting Life	L90 100.000h; L70B20 (Ta,55°C) Lifetime: >54000h of LM-80
Operating Temp.	-20° C - +40° C

Specification Product

Light distribution	Diffused
CRI	>95
SDCM	SDCM<3
Wattage	25Watt/Meter
Voltage	24V DC Parallel Connection
IK Impact	IK08
Weight	
Accessories	Brackets Included
Other Accessories	Cable & Driver not included



CovT Mono

Driver Accessories



Code D021

IP20 60Watt
Input Voltage 220 VAC
Output Voltage 24 Volt
Output Current 2.5 A



Code D022

IP20 75Watt
Input Voltage 220 VAC
Output Voltage 24 Volt
Output Current 3.15 A



Code D023

IP20 100Watt
Input Voltage 220 VAC
Output Voltage 24 Volt
Output Current 6.16 A



Code D028

DALI IP20 240Watt
Input Voltage 24VDC
Output Voltage 24 Volt
Output Current 4 x 5A (max 10A tot.)