


TAP 60 Wall Double

TAP60 is a wall mounted light designed to cast focused upward and downward illumination, delivering clean and precise lighting effects. Its signature cylindrical design, paired with a variety of finishes, offers a perfect blend of functionality and style. Ideal for residential and commercial spaces, it enhances ambiance with subtle, directional lighting tailored to complement modern interiors.







Product Final Code | Select a component for each column for final configuration

Product ID	+	Finishes	+	CTT	+	Optics
TAPWD60		WH White		27K 2700K		SS 11º
		BK Black		30K 3000K		S 15°
		GR Grey		40K 4000K		M 24°
		CT Corten				MF 36°
						F 50°

Configuration Example | TAPWD60.WH.27K.S

licllab.it Data Sheet 1/2



Technical Data

Application | Wall Mounted

Finish Aluminium Powder

Dimensions | Ø 60 x 170 mm

Fitting Life L90 100.000h

L70B20 (Ta,55°C)

Lifetime: > 54.000h of LM-80

Operating

temperature | -20°C / + 55°C

Specification Product

Light Distribution

n | 11° - 15° - 24° - 36° - 50°

CRI > 90

SDCM < 3

Wattage 4 + 4 watt

Voltage 24Volt DC

IK Impact | IK10

Lumen Data

СТТ	Γ Flux Lu	ımen Deliv	ered Lumen
2700	DK 575 +	575 50	06 + 506
3000	OK 631+	631 5	56 + 556
4000	OK 641+	641 5	64 + 564

Accessories

H005



Honeycomb

Drivers

Built-in TRIAC