

ZYRA PRO Adjustable Mono

ZYRA is a wall mounted adjustable light ideal for illuminating facades, walls, and outdoor spaces with elegance and precision. Designed to withstand the most demanding environments, it features an IP67 rating, ensuring waterproofing and resistance to weather conditions. Ideal for architectural and decorative applications, it combines reliable performance with a discreet and functional design.


CRI 90

≤3 MAC ADAM

IP67

220V AC

IK10



Product Final Code | Select a component for each column for final configuration

Product ID	+	Length	+	CTT	+	Optics
ZYPA		1 305 mm		27K 2700K		SS 10°
		2 593 mm		30K 3000K		S 18°
		3 880 mm		40K 4000K		M 30°
		4 1169 mm				MF 45°
						F 60°
						OV 35°x12°
						WW Wall grazer

Configuration Example | ZYPA1.27K.SS

Technical Data

Application	Wall mounted
Finish	Dark grey anodized aluminium
Dimensions	67 x 49 x length
Fitting Life	100.000h L80 B20 (Ta ,25°C) Reported TM-21 L70 Lifetime: >100000 hours

Specification Product

Light Distribution	10° - 18° - 30° - 45° - 60° 35°x12° - Wall washer
CRI	> 90
SDCM	≤ 3
Wattage	50 Watt/meter
Voltage	220 Volt

Lumen Data

CTT	1 ft - 305 mm - 15W Delivered Lumen	2 ft - 593 mm - 30 W Delivered Lumen	3 ft - 880 mm - 45W Delivered Lumen	4 ft - 1169 mm - 60W Delivered Lumen
2700K	1159	2318	3477	4636
3000K	1240	2480	3720	4960
4000K	1240	2480	3720	4960

Driver

Built-in DALI

Brackets

L-BR064



Screw on to the profile

L-BR065



70 mm on wall

L-BR051



150 mm on wall

L-BR050



250 mm on wall

Honeycomb

H001



For 1ft –
305 mm

H011



For 2ft –
593 mm

H013



For 3ft –
880 mm

H015



For 4ft –
1169 mm

Antiglare

L-CON022A



For 1ft –
305 mm

L-CON022B



For 2ft –
593 mm

L-CON022C



For 3ft –
880 mm

L-CON022D



For 4ft –
1169 mm

Cables

Male connector



M23 5x1.5

L-CB135 | L = 500

L-CB139 | L = 1000

L-CB143 | L = 2000

Female connector



M23 5x1.5

L-CB136 | L = 500

L-CB140 | L = 1000

L-CB144 | L = 2000

Male and female extension connector



M23 5x1.5

L-CB148 | L = 500

L-CB149 | L = 1000

L-CB150 | L = 2000