



PERFIL Plus 3040 RGBW Pixel

PERFIL Plus 3040 is designed for indoor and outdoor use, this surface-mounted linear light features a durable extruded aluminum body with IP67 waterproof and IK10 impact resistance. Its polyurethane encapsulation ensures UV protection and longevity. Available in five lengths with an anodized aluminum finish, it delivers diffused mono-color lighting with high-performance 2835 LEDs (CRI>90, SDCM<3). Operating at 12W/m with a 24V constant voltage and integrated ICs, it ensures efficiency and stability.



Product Final Code | Select a component for each column for final configuration

Product ID	+	Length	+	.90	+	CTT
L-PM		6W 1ft 305mm				PIXEL 3000K
		12W 2ft 610mm				
		18W 3ft 915mm				
		24W 4ft 1220mm				
		30W 5ft 1525mm				

Configuration Example | L-PM.3.5W.90.PIXEL

Technical Data

Application	Surface mounted
Dimensions	30 x 40 x length / custom
Finish	Dark grey powder coating
Fitting Life	53.000h L80 B20 (Ta ,25°C) Reported TM-21 L70 Lifetime: > 54000 hours
Operating Temperature	- 20°C / + 50 °C
Addressable	Every 100 mm

Specification Product

Light Distribution	Diffused
CRI	> 90
SDCM	< 3
Wattage	20 Watt/m
Voltage	24 Volt DC
IK impact	IK 10
Brackets	Included

Lumen Data

CTT	6W - 1ft - 305mm Delivered lm/m	12W - 2ft - 610mm Delivered lm/m	18W - 3ft - 915mm Delivered lm/m
3000K	554	1109	1663
CTT	24W - 4ft - 1220mm Delivered lm/m	30W - 5ft - 1525mm Delivered lm/m	
3000K	2218	2772	

Drivers

DMX001	D016	D007	D004
			
DMX 4X120Watt channel	On/Off 150 Watt	On/Off 240 Watt	On/Off 150 Watt

Accessories

Male connector



M12 5x0.35
 L-CB1018 | L = 300
 L-CB1019 | L = 1000
 L-CB1020 | L = 5000

Female connector



M12 5x0.35
 L-CB1021 | L = 300
 L-CB1022 | L = 1000
 L-CB1023 | L = 5000

Male and female extension connector



M12 5x0.35
 L-CB1024 | L = 300
 L-CB1025 | L = 5000